

Attorney's Docket No.: 12950-001001 / 56512US002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: James D. Hansen et al.

Art Unit: 3732

Serial No.: 10/078,970

Examiner: Bumgarner, M.

Filed

: February 18, 2002

Title

: ORTHODONTIC SEPARATORS

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

DECLARATION OF TSI-ZONG TZOU UNDER 37 C.F.R. § 1.132

- I, Tsi-Zong Tzou, declare as follows:
- I am a citizen of the Republic of China and presently live at 713 Pamela Circle, 1. Arcadia, California;
- I received a Bachelor of Science degree in Chemical Engineering from National 2. Taiwan University, Taipei, Taiwan in 1983, a Master of Science degree in Chemical Engineering from West Virginia University, Morgantown, West Virginia in 1985, and a Doctoral degree in Chemical Engineering from State University of New York at Buffalo, Buffalo, New York in 1989;
- 3. I was employed as a Senior Research Engineer at Cortec Corporation from 1990 to 1992;
 - 4. I have been employed by 3M Company since 1992;
- 5. My current position is Product Development Specialist and that my responsibilities include developing orthodontic force modules and bonding adhesives;
 - 6. A list of my articles, patents, and patent applications is attached.
- 7. Orthodontic separators are routinely used to increase the space between teeth before fitting orthodontic bands. Once inserted between adjacent teeth, the separator is under

Applicant: James D. Hansen et al. Attorney's Docket No.: 12950-001001 / 56512US002

Serial No.: 10/078,970

Filed: February 18, 2002

Page : 2 of 3

compression, and due to its tendency to rebound, provides a force to separate the adjacent teeth. This compressive force decreases during the time when the separator is in use. Separators are usually left between adjacent teeth for about a week before fitting bands.

- 8. This invention describes orthodontic separators that exhibit an increase in compressive force when inserted between teeth in the oral environment. The increase in compressive force can be achieved by a separator of an O-ring or dog-bone shape that expands in the oral environment. After the expansion, a larger volume of such a separator is compressed between teeth, and as a result the compressive force increases. The contracted configuration of the separator before the expansion allows for easy insertion of the separator.
- 9. An O-ring shape is preferred because an O-ring encircles the contact point between adjacent teeth so that the pressure is distributed evenly over the entire O-ring and not concentrated only on the contact point. An O-ring better fits the space around the contact point, and therefore has less tendency to fall out over the extended time when the separator is used in patient's mouth.
- 10. A dog bone shape is also preferred. The middle section of the dog bone fits in the tightest space between adjacent teeth where the contact point is, and the end sections of the dog bones fit in the wider space around the contact point. Again the pressure is distributed over a larger area than just the contact point. And the better fit between the dog bone shape and the space around the contact point prevents the separator from falling out during extended time when the separator is in use.
- 11. The increase in compressive force can also be achieved by a separator of a coil or washer shape with shape memory metal alloys. When inserted in the oral environment, the separator changes its shape from a contracted configuration, e.g., flattened coil, to an expanded configuration, e.g., expanded coil. The expanded coil has a tendency to occupy a larger volume and is compressed between teeth, and as a result the compressive force increases.

Attorney's Docket No.: 12950-001001 / 56512US002

Applicant: James D. Hansen et al.

Serial No.: 10/078,970

Filed: February 18, 2002

Page: 3 of 3

12. A coil or washer shape is preferred for shape memory metal alloys because the separator in one shape, e.g., flattened coil, can be inserted between teeth easily, and the separator in another shape, e.g., expanded coil, exhibits an increase in compressive force when it is activated in the oral environment. A coil or washer shape allows the pressure to be distributed over a larger contact area than just the contact point between teeth, and has less tendency to fall our over the extended time when the separator is used in patient's mouth.

- shape does not conform to the interproximal space between adjacent teeth. Although the wedge shape allows an easy insertion through the apex prior to dental filling, it also allows easy removal in the reverse direction of insertion. Consequently, if a wedge shape were chosen for an orthodontic separator, the separator might fall out over the extended period time the separator is used in the patient's mouth. The separator is even more easily lost after the space between adjacent teeth increases over time. As the wedge-shaped separator is asymmetrical, and exerts pressure only on one side of the arch, the wedge shape may cause unwanted rotation over an extended period of time. Additionally, since the dental wedge protrudes beyond the interproximal space between adjacent teeth and causes irritation to surrounding tissues, it is not practical to leave it in the mouth for extended period of time.
- 14. I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the instant patent application or any patent issuing thereon.

Dated: January 18, 2005

Tsi-Zong Tzou

PATENTS

- G.R. Hofmann, N. Jing, T.Z. Tzou and M. W. Muggli, *Elastomeric Dental Article with a Protective Fluoropolymer Layer*, US Patent Application (2004).
- N. Jing, G.R. Hofmann and T.Z. Tzou, *Non-Elastomeric Dental Article with a Protective Fluoropolymer Layer*, US Patent Application (2004).
- M.L. Lai and T.Z. Tzou, Orthodontic System with Resilient Appliances, US Patent Application (2004).
- M.L. Lai and T.Z. Tzou, Method of Orthodontic Treatment, US Patent Application (2004).
- T.Z. Tzou and J.V. Brennen, Containers for Photocurable Materials, US 20030196914 (2003).
- J.D. Hansen and T.Z. Tzou, Orthodontic Separators, US 20030157454 (2003).
- T.Z. Tzou, R.K. Schultz and D.L. Ross, Flunisolide Aerosol Formulations, US Patent 5,980,867 (1999).
- T.Z. Tzou, R.K. Schultz and D.L. Ross, *Flunisolide Aerosol Formulations*, US Patent 5,776,433 (1998).
- B.A. Miksic, T.Z. Tzou and J.M. Foley, *Vapor Phase Corrosion Inhibitor-Desiccant Material*, US Patent 5,209,869 (1993).

PUBLICATIONS

- J.V. Brennen, D. James, P. Soo, and T.Z. Tzou, *The APC Plus Adhesive Coated appliance System: Features and Technical Review*, Orthodontic Perspective XI (1), 3M Unitek, 5-9 (2004).
- T.Z. Tzou, *AlastiK Easy-To-Tie Ligature Development*, Orthodontic Perspective VIII (1), 3M Unitek, 9-10 (2001).
- T.Z. Tzou, Aerodynamic Particle Size of Metered-Dose Inhalers Determined by Quartz Crystal Microbalance and the Andersen Cascade Impactor, Int. J Pharmaceutics 186, 71-79 (1999).
- T.Z. Tzou, R.R. Pachuta, R.B. Coy and R.K. Schultz, Drug Form Selection in Albuterol-Containing Metered-Dose Inhaler Formulations and Its Impact on Chemical and Physical Stability, J. Pharm. Sci. 86 (12), 1352-1357 (1997).
- T.Z. Tzou, Density, Excess Molar Volume, and Vapor Pressure of Propellant Mixtures in Metered-Dose Inhalers: Deviation from Ideal Mixtures, Respiratory Drug Delivery VI, Interpharm Press, 439-443 (1998).
- T.Z. Tzou and J.M. Elvecrog, Deducing the Drug Aerodynamic Particle Size Distribution from the Combined Distribution of Drug and Non-volatile Excipient(s) for MDI Formulations Using the QCM Cascade Impactor, Respiratory Drug Delivery V, Interpharm Press, 414-416 (1996).
- T.Z. Tzou and J.M. Elvecrog, Comparing the Aerodynamic Particle Size of MDIs Measured by the Quartz Crystal Microbalance Cascade Impactor and the Andersen Cascade Impactor, Pharm. Res. 12 (9): S-181 (1995).
- R.K. Schultz, T.Z. Tzou, R.R. Pachuta and R.B. Coy, The Chemical and Physical Stability of Albuterol-Containing Metered Dose Inhaler Formulations: Effects of the Drug Form, Propellant and Cosolvent, Pharm. Res. 11 (10): S-209 (1994).

- T.Z. Tzou and S.W. Weller, Catalytic Oxidation of Dimethyl Methylphosphonate, J. Catalysis 146, 370-374 (1994).
- T.Z. Tzou and R.K. Schultz, Use and Limitation of the Aerosizer in Measuring the Aerodynamic Particle Size of MDI's, Pharm. Res. 10 (10): S167 (1993).
- R.K. Schultz, D.L. Ross and T.Z. Tzou, Assessment of MDI Formulations Based on Medication Delivery Techniques, Pharm. Res. 10 (10): S166 (1993).
- T.Z. Tzou and B.A. Miksic, *Volatile Corrosion Inhibitors for Electronic Materials*, Proc. of the Symposium on Corrosion of Electronic Materials and Devices held in conjunction with the 178th Electrochemical Society Meeting, Seattle, WA, 15-19 Oct., 1990.
- T.Z. Tzou, Oxidation of Dimethyl Methylphosphonate over Platinum-Alumina Catalyst, Ph.D. Dissertation, Advisor: Dr. Sol W. Weller, SUNY/Buffalo, Dept. of Chem. Eng., 1989.
- T.Z. Tzou and S.W. Weller, *Catalytic Destruction of DMMP over Platinum-Alumina*, Proc. 1988 CRDEC Scientific Conference on Chemical Defense Research, Aberdeen Proving Ground, MD, 15-18 Nov., 1988.
- T.Z. Tzou and S.W. Weller, *DMMP Oxidation over Platinum-Alumina: Identification of Liquid Products*, Proc. 1987 CRDEC Scientific Conference on Chemical Defense Research, Aberdeen Proving Ground, MD, 17-20 Nov., 1987.
- T.Z. Tzou, S.W. Weller and C.C. Hsu, *Characterization of Deactivated Oxidation Catalyst*, Proc. 10th North American Meeting of the Catalysis Society, San Diego, CA, 17-22 May, 1987.
- M.J. Hwang, T.Z. Tzou and W.B. Whiting, A Corresponding-States Treatment for the Viscosity of Polar Fluids, 1986 AIChE Annual Meeting, Miami Beach, FL, 2-7 Nov., 1986.
- T.Z. Tzou, Calculation of Viscosities for Polar Fluid Mixtures, M.S. Thesis, Advisor: Dr. Wallace B. Whiting, West Virginia University, Dept. of Chem. Eng., 1985.